




# ImpactBearing.com

LARGEST INVENTORY • IN STOCK OVERNIGHT

**(800) 962-4180**



## Stainless Steel Instrument Quality Radial Open Bearings Inch Series



Impact Part Number	BORE d	O.D. D	WIDTH B	REFERENCE DIAMETER		FILLET RADIUS r	Ball Complement		Load Ratings lbs.		SPEED RATING N <sub>max</sub> /n rpm/1000	BRG. WGT. GMS.	STD. REF.
				L <sub>i</sub>	L <sub>o</sub>		NO. Z	SIZE D <sub>w</sub>	DYN. C <sub>r</sub>	STATIC C <sub>0r</sub>			
SRI-2	.0400	.1250	.0469	.064	.100	.003	6	.025	24	7	192	0.05	R0-9
SRI-2 1/2	.0469	.1562	.0625	.081	.124	.003	6	1/32	37	11	149	0.15	R0
SRI-3	.0550	.1875	.0781	.093	.159	.003	5	3/64	60	18	121	0.20	R1
SRI-4	.0781	.2500	.0937	.122	.193	.003	6	3/64	75	24	97	0.50	R1-4
SRI-3332	.0937	.1875	.0625	.118	.163	.003	7	1/32	44	13	109	0.10	R133
SRI-5	.0937	.3125	.1094	.173	.270	.003	6	1/16	128	42	68	0.85	R1-5
SRI-418	.1250	.2500	.0937	.166	.221	.003	7	1.0mm	66	22	79	0.35	R144
SRI-518	.1250	.3125	.1094	.173	.270	.005	6	1/16	128	42	68	.0.70	R2-5
SRI-618	.1250	.3750	.1094	.173	.270	.005	6	1/16	128	42	68	1.30	R2-6
SSR-2	.1250	.3750	.1562	.200	.320	.012	7	1/16	146	51	61	1.30	R2
SRI-5532	.1562	.3125	.1094	.221	.279	.003	7	3/64	88	33	61	0.65	R155
SRI-5632	.1875	.3125	.1094	.221	.279	.003	7	3/64	88	33	61	0.50	R156
SRI-6632	.1875	.3750	.1250	.235	.343	.003	8	1/16	161	62	54	0.90	R166
SRI-3	.1875	.5000	.1562	.276	.433	.012	7	3/32	295	110	44	2.60	R-3
SRI-614	.2500	.3750	.1250	.285	.340	.003	13	1.0mm	95	46	48	0.65	R168
SRI-814	.2500	.5000	.1250	.330	.431	.005	10	1/16	187	84	40	1.90	R188
SSR-4	.2500	.6250	.1960	.323	.513	.012	8	3/32	331	134	35	4.40	R-4
SRI-1214	.2500	.7500	.2188	.386	.598	.016	6	9/64	542	205	31	8.70	R-4A
SRI-8516	.3125	.5000	.1562	.362	.450	.005	11	1/16	198	95	37	1.60	R1810
SRI-1038	.3750	.6250	.1562	.458	.543	.010	12	1/16	205	84	30	2.60	R620
SRI-1438	.3750	.8750	.2188	.520	.741	.016	7	5/32	743	309	24	8.80	R-6
SRI-1212	.5000	.7500	.1562	.587	.672	.010	16	1/16	238	112	24	3.30	R824
SRI-1458	.6250	.7500	.1562	.713	.798	.010	18	1/16	247	126	20	3.90	R1028
SRI-1634	.7500	1.000	.1562	.837	.922	.010	22	1/16	271	154	17	4.50	R1232

- "Z" Metal shield one side only
- "2RS" Rubber seal two sides

- "ZZ" Metal shield two sides
- Add "CER" prefix for Ceramic

- "RS" rubber seal one side only
- Delete "S" Prefix for Chrome/Steel

- Available in Chrome/Steel

**IMPACT BEARINGS** © 2005 All rights reserved.

**800-962-4180** || Toll Free Fax: 1-888-8BEARING

1291 Puerta Del Sol || San Clemente, CA 92673

Web: <http://impactbearing.com> || Email: [info@impactbearing.com](mailto:info@impactbearing.com)