




ImpactBearing.com

LARGEST INVENTORY • IN STOCK OVERNIGHT


(800) 962-4180



Stainless Steel Radial Shielded And Flanged Shielded Bearings Metric L Series



Shielded 2 Sides



Shielded 2 Sides

Impact Part Number "Open"	Impact Part Number "Flanged"	BORE d	O.D. D	WIDTH B	FLANGE DIAMETER D _f	FLANGE WIDTH B _f	REFERENCE DIAMETER		FILLET RADIUS r	BALL COMPLEMENT		Load Ratings Kgs.		SPEED RATING N _{max} /f _n rpm/1000
							L _j	L _o		NO. Z	SIZE D _w	DYN. C _r	STATIC C _{0r}	
SL-520	SLF-520	2.0	5.0	2.3	6.1	0.5	2.90	4.28	0.08	7	1/32	19	6	112
SL-625	SLF-625	2.5	6.0	2.6	7.1	0.6	3.80	5.23	0.08	8	1/32	21	8	89
SL-630	SLF-630	3.0	6.0	2.5	7.2	0.6	3.80	5.23	0.08	8	1/32	21	8	89
SL-730	SLF-730	3.0	7.0	3.0	8.1	0.8	4.10	6.13	0.10	7	3/64	40	14	78
SL-740	SLF-740	4.0	7.0	2.5	8.2	0.6	4.80	6.33	0.08	11	1/32	26	11	72
SL-840	SLF-840	4.0	8.0	3.0	9.2	0.6	5.20	7.24	0.10	7	3/64	40	15	64
SL-940	SLF-940	4.0	9.0	4.0	10.3	1.0	5.20	7.93	0.10	7	1/16	66	23	61
SL-1040	SLF-1040	4.0	10.0	4.0	11.5	0.8	5.46	8.50	0.15	8	1/16	73	27	54
SL-850	SLF-850	5.0	8.0	2.5	9.2	0.6	5.80	7.26	0.08	13	1/32	28	14	59
SL-950	SLF-950	5.0	9.0	3.0	10.2	0.6	6.00	8.04	0.10	10	3/64	51	21	56
SL-1050	SLF-1050	5.0	10.0	4.0	11.6	0.8	6.40	8.94	0.10	8	1/16	73	25	52
SL-1150	SLF-1150	5.0	11.0	5.0	12.5	1.06	6.40	9.54	0.15	8	1/16	73	29	48
SL-1060	SLF-1060	6.0	10.0	3.0	11.2	0.6	6.95	9.04	0.10	9	3/64	47	20	49
SL-1260	SLF-1260	6.0	12.0	4.0	13.6	0.8	7.70	10.48	0.15	10	1/16	85	37	43
SL-1360	SLF-1360	6.0	13.0	5.0	15.0	1.1	7.33	11.44	0.15	8	2.0mm	111	45	41
SL-1170	SLF-1170	7.0	11.0	3.0	12.2	0.6	8.10	10.14	0.10	9	3/64	46	21	43
SL-1370	SLF-1370	7.0	13.0	4.0	14.6	0.8	8.43	11.54	0.15	11	1/16	90	35	39
SL-1470	SLF-1470	7.0	14.0	5.0	16.0	1.1	9.00	12.45	0.15	9	2.0mm	120	53	37
SL-1280	SLF-1280	8.0	12.0	3.5	13.6	0.8	9.10	11.24	0.10	11	3/64	52	26	39
SL-1480	SLF-1480	8.0	14.0	4.0	15.6	0.8	9.90	12.55	0.15	10	1/16	84	40	35
SL-1680	SLF-1680	8.0	16.0	5.0	18.0	1.1	9.68	14.20	0.20	9	3/32	164	73	32
SL-1790	SLF-1790	9.0	17.0	5.0	19.0	1.1	11.20	15.34	0.20	10	3/32	176	83	30
SL-2090	-	9.0	20.0	6.0	-	-	12.32	17.44	0.30	9	7/64	217	101	27
SL-1910	-	10.0	19.0	7.0	-	-	12.32	17.44	0.30	9	7/64	217	101	27

- "Z" Metal shield one side only
- "2RS" Rubber seal two sides

- "ZZ" Metal shield two sides
- Add "CER" prefix for Ceramic

- "RS" rubber seal one side only
- Delete "S" Prefix for Chrome/Steel

- Available in Chrome/Steel

IMPACT BEARINGS © 2005 All rights reserved.

800-962-4180 || Toll Free Fax: 1-888-8BEARING

1291 Puerta Del Sol || San Clemente, CA 92673

Web: <http://impactbearing.com> || Email: info@impactbearing.com